

ABLOY 4190



Tootekirjeldus

Deadlocking can be controlled by a sliding snib on the forend of the lock case. When the snib is in its up position, the door will be deadlock when closed and can only be opened by a key or by the thumbturn. When the snib is in its down position, the door can be opened by the handles as well.

Fire resistance: suitable for fire doors

Mortice standard: SFS 5209

Compatible products:

- Striker plate: [4690](#), [4691](#), [4692](#), [4693](#), [LP711](#), [LP714](#), [LP721](#), [LP731](#)
- Cylinder: [CY001C](#), [CY001T](#), [CY001U](#), [CY013C](#), [CY013U](#), [CY013T](#), [CY002C](#), [CY002U](#), [CY002T](#), [CY028C](#), [CY028U](#), [CY028T](#), [CY029C](#), [CY029U](#), [CY029T](#), [CY060U](#), [CY060T](#), [CY061U](#), [CY061T](#), [CY062U](#), [CY062T](#)
- Thumbturn: [CH003](#)

TOOTENIMETUS	SOODUS	HIND
ÕšÕ¼Ń€ŃfŃ• ð•ð°ð¼ð°ð° ABLOY 4190/50 Fe/ZL (ð»ðµð²ð°Ń•)	55.08 €	78.68 €
ÕšÕ¼Ń€ŃfŃ• ð•ð°ð¼ð°ð° ABLOY 4190/50 Fe/ZL(ð¿Ń€ð°ð²ð°Ń•)	55.08 €	78.68 €

