

Abloy EL595 FL



Tootekirjeldus

EL595-FL push&pull function lock case for solid doors. According to the standard: EN179.

- Opened with the inside handle
- Operating voltage: 12-24V DC. max current 850mA norm. 300mA
- Bolt throw: 20-14 mm
- Temperature range: -20...+60°C
- Backset: 50mm
- Spindle: 8 mm
- Forend: 22 mm
- Strike plates: LP12, LP22, LP32
- Lead covers: EA280, EA281
- Cable: EA217

Function:

A pull outside, inside handle or handle and pull: door can be opened by pushing or pulling when the electrical control is on (e.g. timer, reader, push button). The inside door handle is electrically controlled and the door will be locked if any kind of input is triggered.

Applications:

- Interior and exterior doors of offices, business premises, hospitals, schools
- Exit doors

- | TOOTENIMETUS | SOODUS | HIND |
|---|--------|-----------|
| <p> DæĐ¾Ñ,Đ¾Ñ€Đ½Ñ«Đ¹ Đ·Đ°Đ¼Đ¾Đ° Abloy EL595FL (Ñ€ÑƒÑ‡Đ°Đ°
 Đ¾Ñ,Đ°Đ»ÑŽÑ‡ĐµĐ½Đ° Đ¿Ñ€Đ, Đ¾Ñ,Đ°Đ»ÑŽÑ‡ĐµĐ½Đ,Đ,
 Đ¿Đ,Ñ,Đ°Đ½Đ,Ñ•) </p> | | 1296.36 € |

