

Abloy PE590



Tootekirjeldus

- Designed For wooden or metal doors.
- 50mm backset.
- Fail locked outside.
- Free egress from inside when handle fitted.
- Meets EN1125 when used with PBE-002 panic bar.

Features:

- Easily reversible deadbolt and trigger bolt
- 14mm Deadbolt
- Inside handle operates at all times or can be controlled electrically in two-way access-controlled doors (electrically controlled handle won't meet EN179 or EN1125)
- Meets EN179 and EN1125 for emergency and panic exits and EN1634-1 for fire resistance doors (when inside handle can be operated at all times and installed with suitable hardware)
- Tested to mechanical resistance standard EN12209
- Tested to draft standards prEN14846
- Retrofits mechanical Scandinavian mortice locks

TOOTENIMETUS	SOODUS	HIND
<p> $\mathbb{D} \propto \mathbb{D}^{3/4} \tilde{N}, \mathbb{D}^{3/4} \tilde{N} \in \mathbb{D}^{1/2} \tilde{N} \cdot \mathbb{D}^1 \mathbb{D} \cdot \mathbb{D}^\circ \mathbb{D}^{1/4} \mathbb{D}^{3/4} \mathbb{D}^\circ$ Abloy PE590 ($\mathbb{D} \pm \mathbb{D} \mu \mathbb{D} \cdot$ $\mathbb{D} \cdot \mathbb{D}^\circ \mathbb{D} \mathbb{D} \mathbb{D}^{3/4} \tilde{N} \in \mathbb{D}^{1/2} \mathbb{D}^{3/4} \mathbb{D}^1 \mathbb{D} \mathbb{D} \gg \mathbb{D}^\circ \mathbb{D}^{1/2} \mathbb{D}^\circ \mathbb{D}, \mathbb{D}, \mathbb{D} \pm \mathbb{D} \mu \mathbb{D} \cdot \mathbb{D}^\circ \mathbb{D}^\circ \mathbb{D} \pm \mathbb{D} \mu \mathbb{D} \gg \tilde{N} \bullet$) </p>		1322.85 €

