

ASSA 851C-35



Tootekirjeldus

ASSA ABLOY motor lock 851C-35 is suitable for narrow profile doors. It is suitable to be used as a night and safety-lock in doors with high security commercial, offices and industrial premises.

Features:

- Opening speed approximately 0.2 seconds
- New hook bolt for increased strength
- and side pressure
- LEDs and switches for initiation / status of the DAC
- The lock can be opened with a key / thumb turn
- Backset 35 mm
- Built-in hidden door position sensor (magnet in the strike plate)
- Can be combined with other Hi-O devices without control, for example daytime lock, automatic doors and card readers.

TOOTENIMETUS	SOODUS	HIND
ASSA Connect 851C-35 $\text{D}^{1/4}\text{D}^{3/4}\text{N}, \text{D}^{3/4}\text{N} \in \text{D}^{1/2}\text{N} \langle \text{D}^1 \text{D} \cdot \text{D}^\circ \text{D}^{1/4}\text{D}^{3/4}\text{D}^\circ$		2806.00 €
ASSA Connect 851C-35 $\text{D}^{1/4}\text{D}^{3/4}\text{N}, \text{D}^{3/4}\text{N} \in \text{D}^{1/2}\text{N} \langle \text{D}^1 \text{D} \cdot \text{D}^\circ \text{D}^{1/4}\text{D}^{3/4}\text{D}^\circ +$ $\text{oN}, \text{D}^2\text{D}_\mu\text{N}, \text{D}^{1/2}\text{N} \langle \text{D}_\mu \text{D}_i \text{D} \rangle \text{D}^\circ \text{D}^{1/2}\text{D}^\circ \text{D}_s + \text{D}_i \text{N} \in \text{D}^{3/4}\text{D}^2\text{D}^{3/4}\text{D}^\circ +$ $\text{D}^\circ \text{D}^\circ \text{D} \pm \text{D}_\mu \text{D} \rangle \text{D}_\mu \text{D}_i \text{N} \in \text{D}^{3/4}\text{N} \text{D}^{3/4}\text{D} \text{N} \langle + \text{N} f \text{N} \cdot \text{N}, \text{N} \in \text{D}^{3/4}\text{D}^1 \text{N} \cdot \text{N}, \text{D}^2\text{D}^{3/4}$ $\text{N} f \text{D}_i \text{N} \in \text{D}^\circ \text{D}^2 \text{D} \rangle \text{D}_\mu \text{D}^{1/2}\text{D}_s \text{N} \bullet + \text{D}^{1/4}\text{D}^\circ \text{D}^3\text{D}^{1/2}\text{D}_s \text{N},$		3172.00 €

